

## MATERIAL SAFETY DATA SHEET

**DP-9203-3**

Version Number 1.0  
Revision Date 04/06/2002

Page 1 of 6  
Print Date 11/4/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

**POLYONE CORPORATION**  
33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE : Product Stewardship (440)-930-1395

Emergency telephone number : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**

Product name : DP-9203-3

Product code : EM10001607

Chemical Name : Mixture

CAS-No. : Mixture

Product Use : Industrial Applications

### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidiny)-, polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	70624-18-9	0.1 - 1
Titanium dioxide	13463-67-7	1 - 5
Talc	14807-96-6	10 - 30

### 3. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See Sections 3 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

**Routes of Exposure:** : Inhalation, Ingestion, Skin contact

#### Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.

Ingestion : May be harmful if swallowed.

Eyes : Resin particles, like other inert materials, are mechanically irritating to eyes.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

## MATERIAL SAFETY DATA SHEET

**DP-9203-3**

Version Number 1.0  
Revision Date 04/06/2002

Page 2 of 6  
Print Date 11/4/2011

**Chronic exposure** : Refer to Section 11 for Toxicological Information.

**Medical Conditions** : None known.

**Aggravated by Exposure:**

#### 4. FIRST AID MEASURES

**Inhalation** : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

**Ingestion** : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.

**Eyes** : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.

**Skin** : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

#### 5. FIRE-FIGHTING MEASURES

**Flash point** : Not applicable

**Flammable Limits**

Upper explosion limit : Not applicable

Lower explosion limit : Not applicable

**Autoignition temperature** : Not relevant

**Suitable extinguishing media** : Carbon dioxide blanket, Water spray, dry powder, foam.

**Special Fire Fighting Procedures** : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

**Unusual Fire/Explosion Hazards** : None

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions** : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

**Environmental precautions** : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.

**Methods for cleaning up** : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

#### 7. HANDLING AND STORAGE

## MATERIAL SAFETY DATA SHEET

**DP-9203-3**

Version Number 1.0  
Revision Date 04/06/2002

Page 3 of 6  
Print Date 11/4/2011

- Handling : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
- Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

- Respiratory protection : No personal respiratory protective equipment normally required.
- Eye/Face Protection : Safety glasses with side-shields.
- Hand protection : Protective gloves.
- Skin and body protection : Long sleeved clothing.
- Additional Protective Measures : Safety shoes.
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Talc	2 mg/m <sup>3</sup>	Time Weighted Average (TWA):	Respirable dust.	ACGIH
Talc	20 mppcf	Time Weighted Average (TWA):	Total dust.	OSHA
Titanium dioxide	10 mg/m <sup>3</sup>	Time Weighted Average (TWA):	Total dust.	ACGIH
Titanium dioxide	15 mg/m <sup>3</sup>	PEL:	Total dust.	OSHA Z1

**9. PHYSICAL AND CHEMICAL PROPERTIES**

- |                     |                  |                  |                   |
|---------------------|------------------|------------------|-------------------|
| Form                | : Solid          | Evaporation rate | : Not applicable. |
| Appearance          | : Pellets, slabs | Specific Gravity | : Not determined  |
| Color               | : WHITE          | Bulk density     | : Not established |
| Odor                | : Very faint     | Vapor pressure   | : Not applicable  |
| Melting point/range | : Not determined | Vapor density    | : Not applicable  |
| Boiling Point:      | : Not applicable | pH               | : Not applicable  |
| Water solubility    | : Insoluble      |                  |                   |

**10. STABILITY AND REACTIVITY**

- Stability : Stable.

## MATERIAL SAFETY DATA SHEET

**DP-9203-3**

Version Number 1.0  
Revision Date 04/06/2002

Page 4 of 6  
Print Date 11/4/2011

- Hazardous Polymerization : Will not occur.
- Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
- Incompatible Materials : Incompatible with strong acids and oxidizing agents.
- Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidiny)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	Highly Toxic	Refer to MSDS for Toxicity Data..
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
14807-96-6	Talc	Systemic effects	Eyes, Respiratory system, Skin.

#### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidiny)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	LC50 Oral LD50	112 mg/m <sup>3</sup> 9,910 mg/kg	rat rat

### 12. ECOLOGICAL INFORMATION

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Chemicals are not readily available as they are bound within the matrix of the polymer.
- Bioaccumulation Potential : Chemicals are not readily available as they are bound within the matrix of the polymer.

## MATERIAL SAFETY DATA SHEET

**DP-9203-3**

Version Number 1.0  
Revision Date 04/06/2002

Page 5 of 6  
Print Date 11/4/2011

Additional advice : Not applicable

**13. DISPOSAL CONSIDERATIONS**

Product : Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

**14. TRANSPORT INFORMATION**

U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground) : Not regulated for transportation.

ICAO/IATA : Not regulated for transportation.

IMO / IMDG : Not regulated for transportation.

**15. REGULATORY INFORMATION**

## US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on the TSCA inventory or are exempt.

California Proposition 65 : This product does not contain a substance listed by California Prop 65.

## Canadian Regulations:

WHMIS Classification : D1A

## WHMIS Ingredient Disclosure List

CAS-No.
544-63-8
57-11-4
14807-96-6
1330-20-7

DSL : Listed.

## MATERIAL SAFETY DATA SHEET

**DP-9203-3**

Version Number 1.0  
Revision Date 04/06/2002

Page 6 of 6  
Print Date 11/4/2011

## National Inventories:

Australia AICS	:	Not determined.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Not determined.

**16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.