

BROWN PIGMENT UV

Version Number 1.0
Revision Date 06/11/2002

Page 1 of 8
Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION
2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE : Product Stewardship, (314) 771-1800
Emergency telephone number : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**

Product name : BROWN PIGMENT UV
 Product code : FO00004509
 Chemical Name : Mixture
 CAS-No. : Mixture
 Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Antimony trioxide	1309-64-4	1 - 5
Lead sulfate	7446-14-2	1 - 5
Carbon black	1333-86-4	5 - 10
Lead chromate	7758-97-6	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory tract.
 Ingestion : May be harmful if swallowed.
 Eyes : May cause eye/skin irritation.
 Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.

BROWN PIGMENT UVVersion Number 1.0
Revision Date 06/11/2002Page 2 of 8
Print Date 11/4/2011

Medical Conditions : None known.
Aggravated by Exposure:

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : No data available.

Flammable Limits
Upper explosion limit : No data available.
Lower explosion limit : No data available.

Autoignition temperature : Not applicable.

Suitable extinguishing media : Carbon dioxide blanket, dry powder, foam, Water spray.

Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

Unusual Fire/Explosion Hazards : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

MATERIAL SAFETY DATA SHEET

BROWN PIGMENT UV

Version Number 1.0

Revision Date 06/11/2002

Page 3 of 8

Print Date 11/4/2011

- Handling : Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
- Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Respiratory protection : Under normal handling conditions a respirator is not required.
- Eye/Face Protection : Safety glasses with side-shields.
- Hand protection : Protective gloves.
- Skin and body protection : Long sleeved clothing.
- Additional Protective Measures : Safety shoes.
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

MATERIAL SAFETY DATA SHEET

BROWN PIGMENT UV

Version Number 1.0

Page 4 of 8

Revision Date 06/11/2002

Print Date 11/4/2011

Components	Value	Exposure time	Exposure type	List:
Antimony trioxide	0.5 mg/m ³	PEL:	as Sb	OSHA Z1
Carbon black	3.5 mg/m ³	Time Weighted Average (TWA):	Total dust. as carbon black	ACGIH
Carbon black	3.5 mg/m ³	PEL:	Total dust. as carbon black	OSHA Z1
Lead chromate	0.012 mg/m ³	Time Weighted Average (TWA):	Dust. as Cr	ACGIH
	0.05 mg/m ³	Time Weighted Average (TWA):	as Pb	ACGIH
Lead chromate	1 mg/m ³	PEL:	as Cr	OSHA Z1
Lead chromate	0.05 mg/m ³	Time Weighted Average (TWA):	Dust. as Pb	OSHA
	0.03 mg/m ³	OSHA Action level:	Dust. as Pb	OSHA
Lead sulfate	0.05 mg/m ³	Time Weighted Average (TWA):	as Pb	ACGIH
Lead sulfate	0.05 mg/m ³	Time Weighted Average (TWA):	as Pb	OSHA
	0.03 mg/m ³	OSHA Action level:	as Pb	OSHA

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: Liquid	Evaporation rate	: Not established
Appearance	: Viscous, Liquid	Specific Gravity	: Not determined
Color	: BROWN	Bulk density	: Not applicable.
Odor	: Very faint	Vapor pressure	: Not determined
Melting point/range	: Not applicable	Vapor density	: Not determined
Boiling Point:	: Not applicable	pH	: Not applicable.
Water solubility	: Immiscible		

10. STABILITY AND REACTIVITY

Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	: Carbon dioxide (CO ₂), carbon monoxide (CO), oxides of nitrogen (NO _x), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

MATERIAL SAFETY DATA SHEET

BROWN PIGMENT UV

Version Number 1.0
Revision Date 06/11/2002

Page 5 of 8
Print Date 11/4/2011

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.
7446-14-2	Lead sulfate	Corrosive	Skin.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
7758-97-6	Lead chromate	Systemic effects	central nervous system, reproductive system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat
1333-86-4	Carbon black	Oral LD50 Dermal LD50	> 15,400 mg/kg > 3 gm/kg	rat rabbit
7758-97-6	Lead chromate	Oral LD50	> 12 gm/kg	mouse

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no
7446-14-2	Lead sulfate	no	2B	no
1333-86-4	Carbon black	no	2B	no
7758-97-6	Lead chromate	no	no	1

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

BROWN PIGMENT UV

Version Number 1.0
Revision Date 06/11/2002

Page 6 of 8
Print Date 11/4/2011

Additional Health Hazard Information:

Lead sulfate 7446-14-2 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

Additional Health Hazard Information:

Lead chromate 7758-97-6 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

12. ECOLOGICAL INFORMATION

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Environmental toxicity has not been established for this mixture as a whole.
- Bioaccumulation Potential : No data available.
- Additional advice : No data available.

13. DISPOSAL CONSIDERATIONS

- Product : Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
- Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

- U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground) : Not regulated for transportation.
- ICAO/IATA : Not regulated for transportation.

MATERIAL SAFETY DATA SHEET

BROWN PIGMENT UV

Version Number 1.0

Page 7 of 8

Revision Date 06/11/2002

Print Date 11/4/2011

IMO / IMDG : Not regulated for transportation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on the TSCA inventory or are exempt.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product
Lead sulfate	7446-14-2	1.78	10lbs	560 LB

California Proposition 65 : WARNING! This product contains a chemical known in the State of California to cause cancer., WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
ANTIMONY COMPOUNDS	1309-64-4	1.07
CHROMIUM VI COMPOUNDS	7758-97-6	32.12
LEAD COMPOUNDS, INORGANIC		
LEAD COMPOUNDS, INORGANIC	7446-14-2	1.78

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
1309-64-4
1333-86-4
7758-97-6
7446-14-2

DSL : Listed.

National Inventories:

BROWN PIGMENT UV

Version Number 1.0

Revision Date 06/11/2002

Page 8 of 8

Print Date 11/4/2011

Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Listed.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.