

SAFETY DATA SHEET

2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 1 of 22
Print Date 09/03/2019

SAFETY DATA SHEET

2530-HH CHARCOAL TOUCH-UP PAINT

Section 1. Identification

GHS product identifier : 2530-HH CHARCOAL TOUCH-UP PAINT
 Chemical name : Mixture
 CAS number : Mixture
 Other means of identification : FO20041975
 Product type : liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : **POLYONE CORPORATION**
 33587 Walker Road, Avon Lake, OH 44012
 1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number (with hours of operation) : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : SKIN IRRITATION - Category 2
 EYE IRRITATION - Category 2A
 CARCINOGENICITY - Category 2

GHS label elements

SAFETY DATA SHEET

2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 2 of 22
Print Date 09/03/2019

Hazard pictograms


Signal word : Warning
Hazard statements : Causes serious eye irritation.
Causes skin irritation.
Suspected of causing cancer.

Precautionary statements

General : Not applicable.
Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Wash hands thoroughly after handling.
Response : IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage : Store locked up.
Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements : None known.
Hazards not otherwise classified : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture
Chemical name : Mixture
Other means of identification : FO20041975

CAS number/other identifiers

Ingredient name	%	CAS number
Methyl ethyl ketone	25 - 50	78-93-3
Tetrahydrofuran	5 - 10	109-99-9

SAFETY DATA SHEET

2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 3 of 22
Print Date 09/03/2019

Xylenes (o-, m-, p- isomers)	1 - 3	1330-20-7
Titanium dioxide	1 - 3	13463-67-7
Carbon black	0 - 0.3	1333-86-4
Ethyl benzene	0 - 0.3	100-41-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person

SAFETY DATA SHEET


2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 4 of 22
Print Date 09/03/2019

feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed
Potential acute health effects

- | | | |
|---------------------|---|---|
| Eye contact | : | Causes serious eye irritation. |
| Inhalation | : | No known significant effects or critical hazards. |
| Skin contact | : | Causes skin irritation. |
| Ingestion | : | No known significant effects or critical hazards. |

Over-exposure signs/symptoms

- | | | |
|---------------------|---|--|
| Eye contact | : | Adverse symptoms may include the following:
pain or irritation
watering
redness |
| Inhalation | : | No specific data. |
| Skin contact | : | Adverse symptoms may include the following:
irritation
redness |
| Ingestion | : | No specific data. |

Indication of immediate medical attention and special treatment needed, if necessary

- | | | |
|-----------------------------------|---|--|
| Notes to physician | : | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments | : | No specific treatment. |
| Protection of first-aiders | : | No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |

See toxicological information (Section 11)

Section 5. Firefighting measures
Extinguishing media

SAFETY DATA SHEET


2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 5 of 22
Print Date 09/03/2019

- Suitable extinguishing media** : In case of fire, use water spray (fog), foam, dry chemical or CO₂.
- Unsuitable extinguishing media** : None known.
- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous thermal decomposition products** : May emit Hydrogen Chloride (HCl).
Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

SAFETY DATA SHEET

**2530-HH CHARCOAL TOUCH-UP PAINT**

Version Number 1.1
Revision Date 08/30/2019

Page 6 of 22
Print Date 09/03/2019

- Large spill** :
- Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage**Precautions for safe handling**

- Protective measures** :
- Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** :
- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** :
- Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection**Control parameters**

SAFETY DATA SHEET


2530-HH CHARCOAL TOUCH-UP PAINT

 Version Number 1.1
 Revision Date 08/30/2019

 Page 7 of 22
 Print Date 09/03/2019

Occupational exposure limits

Ingredient name	Exposure limits
Ethyl benzene	OSHA PEL 1989 (1989-03-01) TWA 435 mg/m ³ 100 ppm STEL 545 mg/m ³ 125 ppm OSHA PEL (1993-06-30) TWA 435 mg/m ³ 100 ppm NIOSH REL (1994-06-01) TWA 435 mg/m ³ 100 ppm STEL 545 mg/m ³ 125 ppm ACGIH TLV (2010-12-06) TWA 20 ppm
Carbon black	OSHA PEL 1989 (1989-03-01) TWA 3.5 mg/m ³ OSHA PEL (1993-06-30) TWA 3.5 mg/m ³ NIOSH REL (1994-06-01) TWA 3.5 mg/m ³ TWA 0.1 mgPAH/m ³ ACGIH TLV (2010-12-06) TWA 3 mg/m ³ Form: Inhalable fraction
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m ³ Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m ³ Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m ³
Xylenes (o-, m-, p- isomers)	OSHA PEL (1993-06-30) TWA 435 mg/m ³ 100 ppm OSHA PEL 1989 (1989-03-01) TWA 435 mg/m ³ 100 ppm STEL 655 mg/m ³ 150 ppm ACGIH TLV (1996-05-18) TWA 434 mg/m ³ 100 ppm STEL 651 mg/m ³ 150 ppm
Tetrahydrofuran	OSHA PEL 1989 (1989-03-01) TWA 590 mg/m ³ 200 ppm STEL 735 mg/m ³ 250 ppm OSHA PEL (1993-06-30)

SAFETY DATA SHEET


2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 8 of 22
Print Date 09/03/2019

	<p>TWA 590 mg/m³ 200 ppm NIOSH REL (1994-06-01) TWA 590 mg/m³ 200 ppm STEL 735 mg/m³ 250 ppm ACGIH TLV (2005-01-01) Absorbed through skin. TWA 50 ppm STEL 100 ppm</p>
Methyl ethyl ketone	<p>OSHA PEL 1989 (1989-03-01) TWA 590 mg/m³ 200 ppm STEL 885 mg/m³ 300 ppm OSHA PEL (1993-06-30) TWA 590 mg/m³ 200 ppm NIOSH REL (1994-06-01) TWA 590 mg/m³ 200 ppm STEL 885 mg/m³ 300 ppm ACGIH TLV (1994-09-01) TWA 590 mg/m³ 200 ppm STEL 885 mg/m³ 300 ppm</p>

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

SAFETY DATA SHEET

2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 9 of 22
Print Date 09/03/2019

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

- Physical state** : liquid [liquid]
Color : GREY
Odor : Not available.
Odor threshold : Not available.
pH : Not available.
Melting point : Not available.
Boiling point : Not available.
Flash point : Not available.
Burning time : Not available.
Burning rate : Not available.
Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive (flammable) limits : **Lower:** Not available.
Upper: Not available.
Vapor pressure : Not available.
Vapor density : Not available.
Relative density : Not available.
Solubility : Not available.
Solubility in water : Not available.
Partition coefficient: n- : Not available.

SAFETY DATA SHEET

2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 10 of 22
Print Date 09/03/2019

octanol/water
Auto-ignition temperature : Not available.
Decomposition temperature : Not available.
SADT : Not available.
Viscosity : **Dynamic:** Not available.
Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.
Chemical stability : Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid : Keep away from extreme heat and oxidizing agents.
Incompatible materials : Avoid contact with acetal homopolymers and acetyl homopolymers during processing.
Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects
Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Xylenes (o-, m-, p- isomers)				
	LD50 Oral	Rat	4,300 mg/kg	-
	LC50 Inhalation	Rat	5,000 ppm	4 h
Remarks - Dermal:	No applicable toxicity data			
Titanium dioxide				
Remarks - Oral:	No applicable toxicity data			
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-
Carbon black				
	LD50 Oral	Rat	15,400 mg/kg	-
Remarks - Inhalation:	No applicable toxicity data			
Remarks - Dermal:	No applicable toxicity data			

SAFETY DATA SHEET

2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 11 of 22
Print Date 09/03/2019

Tetrahydrofuran				
	LD50 Oral	Rat	1,650 mg/kg	-
Remarks - Inhalation:	No applicable toxicity data			
Remarks - Dermal:	No applicable toxicity data			
Methyl ethyl ketone				
	LD50 Oral	Rat	2,737 mg/kg	-
Remarks - Inhalation:	No applicable toxicity data			
	LD50 Dermal	Rabbit	6,480 mg/kg	-
Ethyl benzene				
	LD50 Oral	Rat	3,500 mg/kg	-
Remarks - Inhalation:	No applicable toxicity data			
	LD50 Dermal	Rabbit	5,000 mg/kg	-

Conclusion/Summary : Mixture. Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Xylenes (o-, m-, p- isomers)	Skin - Mild irritant	Rat		8 hrs	-
	Skin - Moderate irritant	Rabbit			-
	Skin - Moderate irritant	Rabbit		24 hrs	-
	Eyes - Mild irritant	Rabbit			-
	Eyes - Severe irritant	Rabbit		24 hrs	-
Titanium dioxide	Skin - Mild irritant	Human		72 hrs	-
Methyl ethyl ketone	Skin - Mild irritant	Rabbit		24 hrs	-
	Skin - Moderate irritant	Rabbit		24 hrs	-
	Skin - Mild irritant	Rabbit		24 hrs	-
Ethyl benzene	Skin - Mild irritant	Rabbit		24 hrs	-
	Eyes - Severe irritant	Rabbit			-

Conclusion/Summary
Skin : Mixture. Not fully tested.

SAFETY DATA SHEET

2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 12 of 22
Print Date 09/03/2019

Eyes : Mixture.Not fully tested.
Respiratory : Mixture.Not fully tested.

Sensitization

Conclusion/Summary
Skin : Mixture.Not fully tested.
Respiratory : Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Xylenes (o-, m-, p-isomers)		3	
Titanium dioxide		2B	
Carbon black		2B	
Tetrahydrofuran		2B	
Ethyl benzene		2B	

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name	Result
Ethyl benzene	ASPIRATION HAZARD - Category 1

Information on likely routes of : Not available.

SAFETY DATA SHEET

2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 13 of 22
Print Date 09/03/2019

exposure

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
Inhalation : No known significant effects or critical hazards.
Skin contact : Causes skin irritation.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness
Inhalation : No specific data.
Skin contact : Adverse symptoms may include the following:
 irritation
 redness
Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Short term exposure**

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Long term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

- Conclusion/Summary** : Mixture. Not fully tested.
General : No known significant effects or critical hazards.
Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity : No known significant effects or critical hazards.
Teratogenicity : No known significant effects or critical hazards.
Developmental effects : No known significant effects or critical hazards.
Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

SAFETY DATA SHEET

2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 14 of 22
Print Date 09/03/2019

Acute toxicity estimates

Route	ATE value
Oral	4,844.6 mg/kg
Route	ATE value
Inhalation (gases)	236,082.9 ppm

Section 12. Ecological information
Toxicity

Product/ingredient name	Result	Species	Exposure
Xylenes (o-, m-, p- isomers)			
	Acute LC50 13.4 Mg/l Fresh water	Fish - Fish	96 h
Remarks - Acute - Fish:	Acute		
	Acute LC50 8.5 Mg/l Marine water	Aquatic invertebrates. Crustaceans	48 h
Remarks - Acute - Aquatic invertebrates.:	Acute		
Remarks - Acute - Aquatic plants:	No applicable toxicity data		
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic - Aquatic invertebrates.:	No applicable toxicity data		
Titanium dioxide			
	Acute LC50 > 1,000 Mg/l Marine water	Fish - Fish	96 h
Remarks - Acute - Fish:	Acute		
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
Remarks - Acute - Aquatic invertebrates.:	Acute		
	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
Remarks - Acute - Aquatic invertebrates.:	Acute		
Remarks - Acute - Aquatic plants:	No applicable toxicity data		
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic - Aquatic invertebrates.:	No applicable toxicity data		

SAFETY DATA SHEET

2530-HH CHARCOAL TOUCH-UP PAINT

 Version Number 1.1
 Revision Date 08/30/2019

 Page 15 of 22
 Print Date 09/03/2019

Carbon black			
Remarks - Acute - Fish:	No applicable toxicity data		
	Acute EC50 37.563 Mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
Remarks - Acute - Aquatic invertebrates.:	Acute		
Remarks - Acute - Aquatic plants:	No applicable toxicity data		
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic - Aquatic invertebrates.:	No applicable toxicity data		
Tetrahydrofuran			
	Acute LC50 2,160 Mg/l Fresh water	Fish - Fish	96 h
Remarks - Acute - Fish:	Acute		
Remarks - Acute - Aquatic invertebrates.:	No applicable toxicity data		
Remarks - Acute - Aquatic plants:	No applicable toxicity data		
	Chronic NOEC 367 Mg/l Fresh water	Fish - Fish	33 d
Remarks - Chronic - Fish:	Chronic		
Remarks - Chronic - Aquatic invertebrates.:	No applicable toxicity data		
Methyl ethyl ketone			
	Acute LC50 3,220 Mg/l Fresh water	Fish - Fish	96 h
Remarks - Acute - Fish:	Acute		
	Acute EC50 5.091 Mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
Remarks - Acute - Aquatic invertebrates.:	Acute		
	Acute EC50 > 500 Mg/l Marine water	Aquatic plants - Algae	96 h
Remarks - Acute - Aquatic plants:	Acute		
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic - Aquatic invertebrates.:	No applicable toxicity data		
Ethyl benzene			
	Acute LC50 4.2 Mg/l Fresh water	Fish - Fish	96 h
Remarks - Acute - Fish:	Acute		
	Acute EC50 6.53 Mg/l Marine water	Aquatic invertebrates. Crustaceans	48 h

SAFETY DATA SHEET

2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 16 of 22
Print Date 09/03/2019

Remarks - Acute - Aquatic invertebrates.:	Acute		
	Acute EC50 2.93 Mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
Remarks - Acute - Aquatic invertebrates.:	Acute		
	Acute EC50 4.6 Mg/l Fresh water	Aquatic plants - Algae	72 h
Remarks - Acute - Aquatic plants:	Acute		
	Acute EC50 3.6 Mg/l Fresh water	Aquatic plants - Algae	96 h
Remarks - Acute - Aquatic plants:	Acute		
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic - Aquatic invertebrates.:	No applicable toxicity data		

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Xylenes (o-, m-, p- isomers)	3.15	8.10 - 25.90	low
Tetrahydrofuran	0.45	-	low
Methyl ethyl ketone	0.29	-	low
Ethyl benzene	3.6	-	low

Mobility in soil

Soil/water partition coefficient (KOC) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local

SAFETY DATA SHEET

2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 17 of 22
Print Date 09/03/2019

authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Listed

Ingredient	CAS #	Status	Reference number
Methyl ethyl ketone	78-93-3	Listed	
Tetrahydrofuran	109-99-9	Listed	
Xylenes (o-, m-, p- isomers)	1330-20-7	Listed	

Section 14. Transport information

U.S.DOT 49CFR
Ground/Air/Water
Proper Shipping Name: Paint
Technical Name:
Hazard Class / Division 3
UN Number UN1263
Packing Group II
Label Required 3

International Air ICAO/IATA Consult mode specific transport rules

International Water IMO/IMDG Consult mode specific transport rules

Section 15. Regulatory information

SAFETY DATA SHEET

2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 18 of 22
Print Date 09/03/2019

U.S. Federal regulations	<p>: United States - TSCA 12(b) - Chemical export notification: None of the components are listed.</p> <p>United States - TSCA 4(a) - Final Test Rules: Not listed</p> <p>United States - TSCA 4(a) - ITC Priority list: Not listed</p> <p>United States - TSCA 4(a) - Proposed test rules: Not listed</p> <p>United States - TSCA 4(f) - Priority risk review: Not listed</p> <p>United States - TSCA 5(a)2 - Final significant new use rules: Not listed</p> <p>United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed</p> <p>United States - TSCA 5(e) - Substances consent order: Not listed</p> <p>United States - TSCA 6 - Final risk management: Not listed</p> <p>United States - TSCA 6 - Proposed risk management: Not listed</p> <p>United States - TSCA 8(a) - Chemical risk rules: Not listed</p> <p>United States - TSCA 8(a) - Dioxin/Furane precursor: Not listed</p> <p>United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined</p> <p>United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed Tetrahydrofuran</p> <p>United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed</p> <p>United States - TSCA 8(d) - Health and safety studies: Not listed</p> <p>United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Ethyl benzene Benzene, methyl-</p> <p>United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Listed</p> <p>United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed</p> <p>United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed</p> <p>United States - Department of commerce - Precursor chemical: Not listed</p>
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	<p>: Listed</p>
Clean Air Act Section 602 Class I Substances	<p>: Not listed</p>
Clean Air Act Section 602 Class II Substances	<p>: Not listed</p>
DEA List I Chemicals (Precursor Chemicals)	<p>: Not listed</p>
DEA List II Chemicals (Essential Chemicals)	<p>: Listed</p>

SAFETY DATA SHEET

2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 19 of 22
Print Date 09/03/2019

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component
Tetrahydrofuran	109-99-9	1,000 lb(s) 454 kg
Methyl ethyl ketone	78-93-3	5,000 lb(s) 2,270 kg 2,270 kg 5,000 lb(s)

SARA 311/312

Classification : SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2A
CARCINOGENICITY - Category 2

Composition/information on ingredients

Name	%	Classification
Ethyl benzene	> 0 - <= 0.3	FLAMMABLE LIQUIDS - Category 3 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2 ASPIRATION HAZARD - Category 1
Carbon black	> 0 - <= 0.3	CARCINOGENICITY - Category 2
Titanium dioxide	>= 1 - <= 3	CARCINOGENICITY - Category 2
Xylenes (o-, m-, p- isomers)	>= 1 - <= 3	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY - inhalation - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A
Tetrahydrofuran	>= 5 - <= 10	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY - oral - Category 4 CARCINOGENICITY - Category 2
Methyl ethyl ketone	>= 25 - <= 50	FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

SAFETY DATA SHEET


2530-HH CHARCOAL TOUCH-UP PAINT

 Version Number 1.1
 Revision Date 08/30/2019

 Page 20 of 22
 Print Date 09/03/2019
SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 3
	Ethyl benzene	100-41-4	0 - 0.3
Supplier notification	Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 3
	Ethyl benzene	100-41-4	0 - 0.3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations**Massachusetts**

: None of the components are listed.

New York

: The following components are listed:

 Ethyl benzene
 Xylenes (o-, m-, p- isomers)
 Tetrahydrofuran
 Methyl ethyl ketone
New Jersey

: The following components are listed:

 Ethyl benzene
 Carbon black
 Isopropanol
 Titanium dioxide
 Xylenes (o-, m-, p- isomers)
 Tetrahydrofuran
 Methyl ethyl ketone
Pennsylvania

: The following components are listed:

 Carbon black

 Isopropanol

 Titanium dioxide

 Xylenes (o-, m-, p- isomers)

 Silica gel

 Ethyl benzene

 Methyl ethyl ketone

SAFETY DATA SHEET

2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 21 of 22
Print Date 09/03/2019

Tetrahydrofuran

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Titanium dioxide, Carbon black, Ethyl benzene, which are known to the State of California to cause cancer, and Benzene, methyl-, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Ethyl benzene	No.	No.
Carbon black	No.	No.
Benzene, methyl-	No.	No.
Titanium dioxide	No.	No.

United States inventory (TSCA 8b) : All components are listed or exempted.

Canada inventory : All components are listed or exempted.

International regulations**Inventory list**

Australia : Not determined.
Canada : All components are listed or exempted.
China : Not determined.
Europe inventory : Not determined.
Japan : Not determined.
New Zealand : Not determined.
Philippines : Not determined.
Republic of Korea : Not determined.
Taiwan : Not determined.
Turkey : Not determined.
United States : All components are listed or exempted.

Section 16. Other information
Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		0
Physical hazards		0

SAFETY DATA SHEET

2530-HH CHARCOAL TOUCH-UP PAINT

Version Number 1.1
Revision Date 08/30/2019

Page 22 of 22
Print Date 09/03/2019

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

Date of printing	:	09/03/2019
Date of issue/Date of revision	:	08/30/2019
Date of previous issue	:	11/07/2018
Version	:	1.1
Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.